

RECEIVED
CENTRAL FAX CENTER

DEC 08 2006

PATENT
P57047IN THE CLAIMS

Please amend claims 34, 39, 40, 41,, 43, 44, 47, 48, 51, 52 and 53 as follows:

1 Claims 1-33. (Canceled)

1 34. (Currently Amended) A method of manufacturing a bubble-jet type ink jet printhead,
2 comprising:

3 depositing, patterning, and etching a resistive material on a silicon substrate;
4 depositing, patterning, and etching an individual signal line over a portion of said resistive
5 material;

6 depositing a first electrically insulating layer over said silicon substrate;
7 etching a hole in said first electrically insulating layer exposing a portion of said resistive
8 material absent of said individual signal line;

9 depositing, patterning, and etching a common signal line, said common signal line being in
10 electrical contact with said resistive material via said hole in said first electrically insulating layer;

11 depositing a second electrically insulating layer over said silicon substrate;
12 etching through a portion of said first and second insulating layers to expose a portion of said
13 individual signal line in a region absent of said resistive material;

14 depositing, patterning, and etching a film to form a plurality of barrier chamber walls, a first
15 of said plurality of barrier walls being on top of a substantial portion of said individual signal line,
16 and a second of said plurality of barrier chamber walls being parallel to said first of said plurality of
17 barrier chamber walls, said second of said plurality of barrier chamber walls being on an opposite

PATENT
P57047

18 side of said hole in said first insulating layer than said first of said plurality of barrier chamber walls;

19 and

20 attaching a nozzle plate to a top portion of said plurality of barrier chamber walls, said nozzle
21 plate being perforated by a plurality of nozzle holes, one of said plurality of nozzle holes being
22 directly above said hole in said first insulating layer.

1 35. (Previously Presented) The method of claim 34, said resistive material is patterned to
2 be "P" shaped.

1 36. (Previously Presented) The method of claim 35, said individual line covers a straight
2 portion of said "P" shaped resistive layer.

1 37. (Previously Presented) The method of claim 36, said hole in said first insulating layer
2 is located over a center of a curved portion of said "P" shaped resistive layer.

1 38. (Previously Presented) The method of claim 37, one unit heater is located between one
2 side of said center of said curved portion of said resistive layer and said straight portion of said
3 resistive layer and another unit heater is located between another side of said center of said curved
4 portion of said resistive layer and said straight portion.

1 39. (Currently Amended) A method of manufacturing a bubble-jet type ink jet printhead,
2 comprising:

PATENT
P57047

3 forming a plurality of resistive heater elements comprised of patterned resistive material on
4 a substrate;

5 forming a patterned electrode layer on the substrate, the patterned electrode layer being
6 electrically connected to the resistive heater elements;

7 forming barrier chamber walls over the substrate, the barrier chamber walls separating pairs
8 of patterned resistive heater elements from each other; and

9 attaching a nozzle plate to a top of the plurality of barrier chamber walls, the nozzle plate
10 being perforated by a plurality of nozzle holes, each nozzle hole being disposed above a portion of
11 the substrate between a pair of patterned resistive heater elements, each nozzle hole also being
12 disposed between a pair of adjacent barrier chamber walls.

1 40. (Currently Amended) The method of claim 39, further comprising forming an insulating
2 layer over the substrate, over the resistive heater elements and over the patterned electrode layer, the
3 plurality of barrier chamber walls being formed on the insulating layer.

1 41. (Currently Amended) The method of claim 39, the resistive heater elements being
2 formed in pairs, wherein barrier chamber walls serve to separate one pair of resistive heating
3 elements from another adjacent pair of resistive heater elements.

1 42. (Previously Presented) The method of claim 39, said electrode layer is deposited so that
2 each pair of resistive heaters are electrically connected in series.

PATENT
P57047

1 43. (Currently Amended) A method of manufacturing a bubble-jet type ink jet printhead,
2 comprising:

3 forming a plurality of resistive heater elements comprised of patterned resistive material on
4 a substrate;

5 forming a patterned first electrode layer on the substrate, the patterned first electrode layer
6 being electrically connected to the resistive heater elements;

7 forming a first insulating layer over the substrate, the plurality of resistive heater elements
8 and the patterned first electrode layer;

9 etching a hole perforating the first insulating layer to expose a portion of each resistive heater
10 element;

11 forming a second electrode layer over the first insulating layer, said second electrode layer
12 being formed in said hole to form electrical contact to each resistive heater element;

13 forming barrier chamber walls over the substrate, the barrier chamber walls separating pairs
14 of patterned resistive heater elements from each other; and

15 attaching a nozzle plate to a top of the plurality of barrier chamber walls, the nozzle plate
16 being perforated by a plurality of nozzle holes.

1 44. (Currently Amended) The method of claim 43, further comprising forming a second
2 insulating layer over the first insulating layer and over the second electrode layer, wherein the barrier
3 chamber walls are formed on the second insulating layer.

1 45. (Previously Presented) The method of claim 43, said hole being formed over a portion

PATENT
P57047

2 of a resistive heater that is not covered by the first electrode layer.

1 46. (Previously Presented) The method of claim 44, further comprising etching back a
2 portion of the second insulating layer to expose a portion of the first electrode layer.

1 47. (Currently Amended) The method of claim 39, the barrier chamber walls being adapted
2 to group together said plurality of resistive heater elements in pairs.

1 48. (Currently Amended) The method of claim 39, ones of resistive heater elements within
2 one pair of resistive heater elements not being separated from each other by the barrier chamber
3 walls.

1 49. (Previously Presented) The method of claim 39, wherein pairs of the plurality of
2 resistive heater elements are dedicated solely to corresponding ones of said plurality of nozzle holes.

1 50. (Previously Presented) The method of claim 39, wherein there is a two to one
2 correspondence between the resistive heater elements and the nozzle holes.

1 51. (Currently Amended) The method of claim 39, each of said barrier chamber walls
2 separating one pair of said resistive heating elements from other adjoining pairs of said resistive
3 heater elements while separating individual ones of said nozzle holes from adjoining others of said
4 nozzle holes.

PATENT
P57047

1 52. (Currently Amended) The method of claim 51, wherein ones of each pair of resistive
2 heater elements are not separated from each other by said ~~barrier~~ chamber walls.

1 53. (Currently Amended) The method of claim 39, each of said ~~barrier~~ chamber walls are
2 rectangular in shape and having rectangular cross sections.